







SHORT-RANGE	Art-Nr. Art-No.	Beschreibung Description	Ausführung Version
	A200-01	<b>SR28A</b> air coil 28x4mm, CuEm 0,28  Leseabstand/read-range: - glass tag 13x3mm : 5cm - tear shape : 8cm - ISO card : 10cm - LR ISO card : 15cm - LR Clamshell : 18cm	* Luftspule * Anschlußkabel: L=0,5m (Zwillingslitze)
	A200-02	<b>SR30A</b> air coil 30x2mm, CuAg 0,12  Leseabstand/read-range: - glass tag 13x3mm : 7cm - tear shape : 10cm - ISO card : 12cm - LR ISO card : 17cm - LR Clamshell : 20cm  * Interne antenne! Nur für OEM Board	* Luftspule
	A200-03	<b>SR22AT</b> air coil 22x4mm, CuAg 0,10  Blocking-Abstand/blocking-range: - glass tag 13x3mm : 4cm - tear shape : 6cm - ISO card : 8cm  * Anti-Transponder(RFID Bloker) Antenne	  Weitere Ausführungen: * Ferritekern-SMD 15x5x2 * Ferritekern-SMD 10x2x2 (Auf Rolle -3k) * SR30AT, MR50AT, MR70AT
MIDDLE-RANGE			
	A200-04	<b>MR50A</b> air coil 50x2mm, CuEm 0,28  Leseabstand / read-range: - glass tag 13x3mm : 10cm - tear shape : 15cm - ISO card : 17cm - LR ISO card : 20cm - LR Clamshell : 24cm	* Luftspule * Anschlußkabel: L=0,5m (Zwillingslitze)
	A200-05	<b>MR70A</b> air coil 70x3mm, CuEm 0,28  Leseabstand/read-range: - glass tag 13x3mm : 11cm - tear shape : 17cm - ISO card : 20cm - LR ISO card : 24cm - LR Clamshell : 28cm	* Luftspule * Anschlußkabel: L=0,5m (Zwillingslitze)